Palmer SuperSet Mirro-Mastic®

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022
Issue date: 6/30/2025 Revision date: 6/30/2025 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : Palmer SuperSet Mirro-Mastic®
Product code : Not available

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Sealant

1.4. Supplier's details

Manufacturer
Palmer Products Corporation
146 St. Matthews Avenue
Louisville, KY, 40207 - USA
T 502.893.3668 Toll-Free: 800.431.6151
palmer@mirro-mastic.com

1.5. Emergency phone number

Emergency number : Medical Emergency Phone Number (CHEMTREC): 1-800-424-9300 (24 Hours),
Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300 (24 Hours)

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Skin corrosion/irritation, Category 2
Serious eye damage/eye irritation, Category 2A
Skin sensitization, Category 1
Germ cell mutagenicity, Category 2
Reproductive toxicity, Category 1B
Specific target organ toxicity, Single exposure, Category 1
Specific target organ toxicity, Repeated exposure, Category 1

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :

Signal word (GHS) : Danger
Hazard statements (GHS) : Causes skin irritation
May cause an allergic skin reaction
Causes serious eye irritation
Suspected of causing genetic defects.
May damage fertility or the unborn child.

Precautionary statements (GHS)	:	Causes damage to organs (thymus). Causes damage to organs (immune system) through prolonged or repeated exposure Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust, fume, gas, mist, vapours, spray. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves, protective clothing, eye and face protection. If exposed or concerned: Call a poison center or doctor. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Store locked up. Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

Not applicable

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%Weight
Limestone	Limestone Chalk / Limestone (A noncombustible solid characteristic of sedimentary rock. It consists primarily of calcium carbonate.) / Natural calcium carbonate / Marble / Calcium carbonate / Limestone (sedimentary rock) / Calcite / Limestone ground / Acetate, 4-methyl-2-propyl-2H-tetrahydropyran-4-yl / Ground limestone	CAS-No.: 1317-65-3	10 - 30

Name	Chemical name / Synonyms	Product identifier	%Weight
N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine	N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine Ethane-1,2-diamine, N-[3-(trimethoxysilyl)propyl]- / 1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]- / Ethylenediamine, N-(3-(trimethoxysilyl)propyl)- / N-(3-(Trimethoxysilyl)propyl)ethylenediamine / Ethylenediamine, N-[3-(trimethoxysilyl)propyl]- / 1,2-Ethylenediamine, N-[3-(trimethoxysilyl)propyl]- / 1,2-Ethanediamine, N-(3-(trimethoxysilyl)propyl)- / 1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]- / 3-(2-Aminoethylamino)propyltrimethoxysilane / N1-[3-(Trimethoxysilyl)prop-1-yl]ethane-1,2-diamine / (Trimethoxysilylpropyl)ethylenediamine / N-.beta.-(Aminoethyl)-.gamma.-aminopropyltrimethoxysilane / N-[3-(Trimethoxysilyl)propyl]ethylenediamine	CAS-No.: 1760-24-3	0.5 - 1.5
Silane, ethenyltrimethoxy-	Silane, ethenyltrimethoxy- Ethenyltrimethoxysilane / Silane, trimethoxyvinyl- / Trimethoxyvinylsilane / Vinyltrimethoxysilane / Ethenyl(trimethoxy)silane	CAS-No.: 2768-02-7	0.5 - 1.5
Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-	Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)- Dibutylbis(pentane-2,4-dionato-O,O')tin / Dibutyl bis(2,4-pentanedionate)tin / Tin, dibutylbis(2,4-pentanedionato-O,O')- / Tin, dibutylbis(2,4-pentanedionato-.kappa.O,.kappa.O')-, (OC-6-11)- / Tin, dibutylbis(2,4-pentanedionato-.kappa.O2,.kappa.O4)-, (OC-6-11)- / Dibutyltin bis(2,4-pentanedionate) / Dibutyltin bis(acetylacetonate) / Di-n-butyltin bis(acetylacetonate)	CAS-No.: 22673-19-4	0.1 - 1

Name	Chemical name / Synonyms	Product identifier	%Weight
Quartz	Quartz Quartz (SiO2) / Silica, crystalline, quartz / Crystalline silica, quartz / .alpha.-Quartz / Silica, crystalline, .alpha.-quartz / QUARTZ / Crystalline silica in the form of quartz / Quartz, silica / Quartz (respirable fraction) / Silica dust / Silica, crystalline-.alpha.quartz / Silica, .alpha.-quartz / Silicon dioxide / Silica, quartz / Silica, crystalline / Quartz (crystalline silica) / Silica dust, crystalline / QUARTZ POWDER / Silica, crystalline (quartz)	CAS-No.: 14808-60-7	0.1 - 1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : IF exposed or concerned: Call a POISON CENTER/doctor.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects : Causes damage to organs (thymus).

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic symptoms : Suspected of causing genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs (immune system) through prolonged or repeated exposure.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5 Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Nitrogen oxides. Aldehydes. Methanol. Irritating vapours.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

For non-emergency personnel

No additional information available

For emergency responders

Environmental precautions : Avoid release to the environment. Prevent entry to sewers and public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Do not breathe dust, fume, gas, mist, spray, vapours. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.

Hygiene measures : Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store away from heat. Store in a cool, dry, place away from incompatible materials. Store locked up.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Limestone (1317-65-3)	
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	10 mg/m³ (total dust) 5 mg/m³ (respirable dust)

Quartz (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	0.025 mg/m³ (respirable particulate matter)
ACGIH chemical category	Suspected Human Carcinogen
USA - OSHA - Occupational Exposure Limits	
Local name	Quartz (Total Dust) (Silica: Crystalline)
OSHA PEL TWA	50 µg/m³ (Respirable crystalline silica)
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
USA - IDLH - Occupational Exposure Limits	
IDLH	50 mg/m³ (respirable dust)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	0.05 mg/m³ (respirable dust)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds. Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.

Eye protection:

Wear eye/face protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle in accordance with good industrial hygiene and safety procedures.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	:	Solid
Appearance	:	Opaque. Paste.
Colour	:	No data available
Odour	:	Mint-like
Odour threshold	:	Mild.
pH	:	No data available
Melting point	:	No data available
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	No data available
Flammability (solid, gas)	:	Non flammable.
Vapour pressure	:	No data available
Relative vapour density at 20°C/ 68 °F	:	No data available
Relative density	:	No data available
Density	:	1.5 – 1.7 g/ml
Solubility	:	Insoluble in water
Partition coefficient n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity, kinematic	:	No data available
Explosive limits	:	No data available
Particle characteristics	:	No data available

N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine	
Flash point	98 °C Atm. press.: 101,3 kPa

Silane, ethenyltrimethoxy-	
Boiling point	123 °C Atm. press.: 1013 hPa Decomposition: 'no'
Flash point	23 °C (closed cup)
Vapour pressure	11.9 hPa Temp.: 20 °C

Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-	
Flash point	87 °C Atm. press.: 1007,8 hPa
Vapour pressure	0.038 Pa Temp.: 25 °C

Quartz	
Boiling point	2230 °C

9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content : < 23 g/l (less water and exempt solvents)

SECTION 10 Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Incompatible materials.

10.5. Incompatible materials

Strong oxidizing agents. Water. Moisture.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Nitrogen oxides. Aldehydes. Methanol. Irritating vapours.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine (1760-24-3)	
LD50 oral rat	2413 mg/kg (Source: EPA_HPV)
LD50 dermal rabbit	> 2009 mg/kg (Source: ECHA_API)
LC50 inhalation rat	1.49 – 2.44 mg/l air Animal: rat, Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity), Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Silane, ethenyltrimethoxy- (2768-02-7)	
LD50 oral rat	7340 µl/kg (Source: NLM_CIP)
LD50 dermal rabbit	3.54 ml/kg (Source: ECHA_API)
LC50 inhalation rat	16.8 mg/l/4h

Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)- (22673-19-4)	
LD50 oral rat	1864 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 1039 - 3344
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Suspected of causing genetic defects.

Carcinogenicity : Not classified.
Not expected to present a significant hazard under anticipated conditions of normal use. Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.

Reproductive toxicity : May damage fertility or the unborn child.

Silane, ethenyltrimethoxy- (2768-02-7)	
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)
NOAEL (animal/female, F0/P)	250 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)

STOT-single exposure : Causes damage to organs (thymus).

Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)- (22673-19-4)	
STOT-single exposure	Causes damage to organs.

STOT-repeated exposure : Causes damage to organs (immune system) through prolonged or repeated exposure.

Limestone (1317-65-3)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine (1760-24-3)	
NOAEL (oral, rat, 90 days)	≥ 500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (dermal, rat/rabbit, 90 days)	≥ 1545 mg/kg bodyweight Animal: rat
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Silane, ethenyltrimethoxy- (2768-02-7)	
LOAEL (oral, rat, 90 days)	62.5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 90 days)	< 62.5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)- (22673-19-4)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified.

Palmer SuperSet Mirro-Mastic®	
Viscosity, kinematic	No data available

Limestone (1317-65-3)	
Viscosity, kinematic	No data available

N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine (1760-24-3)	
Viscosity, kinematic	3.1 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'

Silane, ethenyltrimethoxy- (2768-02-7)	
Viscosity, kinematic	0.7 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'
Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)- (22673-19-4)	
Viscosity, kinematic	1410.671 mm²/s
Quartz (14808-60-7)	
Viscosity, kinematic	No data available

Symptoms/effects : Causes damage to organs (thymus).

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic symptoms : Suspected of causing genetic defects. May damage fertility or the unborn child. Causes damage to organs (timmune system) through prolonged or repeated exposure.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Hazardous to the aquatic environment, short–term (acute) : Not classified.

Hazardous to the aquatic environment, long–term (chronic) : Not classified.

N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine (1760-24-3)	
LC50 - Fish [1]	597 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	81 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	126 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	352 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

Silane, ethenyltrimethoxy- (2768-02-7)	
LC50 - Fish [1]	191 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [not specified] Source: ECHA)
EC50 - Crustacea [1]	168.7 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 957 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	52.4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	28.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)- (22673-19-4)	
LC50 - Fish [1]	> 2 mg/l (Exposure time: 96 h - Species: Oryzias latipes [semi-static] Source: ECHA)
EC50 - Crustacea [1]	0.0036 mg/l Test organisms (species): Daphnia magna

Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)- (22673-19-4)	
EC50 72h - Algae [1]	> 2 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

12.2. Persistence and degradability

Palmer SuperSet Mirro-Mastic®	
Persistence and degradability	Not established.

Limestone (1317-65-3)	
Persistence and degradability	Rapidly degradable

N-[3-(Trimethoxysilyl)propyl]-1,2-ethanediamine (1760-24-3)	
Persistence and degradability	Rapidly degradable

Silane, ethenyltrimethoxy- (2768-02-7)	
Persistence and degradability	Rapidly degradable

Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)- (22673-19-4)	
Persistence and degradability	Rapidly degradable

Quartz (14808-60-7)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

Palmer SuperSet Mirro-Mastic®	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified.

Fluorinated greenhouse gases : No

Other information : No other effects known.

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. The generation of waste should be avoided or minimised wherever possible.

SECTION 14 Transport information

In accordance with DOT / TDG

14.1. UN Number

UN-No. (DOT) : Not regulated

UN-No. (TDG) : Not regulated

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Not regulated
Proper Shipping Name (TDG) : Not regulated

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : Not regulated

TDG
Transport hazard class(es) (TDG) : Not regulated

14.4. Packing group

Packing group (DOT) : Not regulated
Packing group (TDG) : Not regulated

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT
Not regulated

TDG
Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. State regulations

WARNING: This product can expose you to chemicals including Silica, respirable crystalline, which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other Information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022
Revision date : 6/30/2025
Issue date : 6/30/2025
Other information : None.

Prepared by : Nexreg Compliance Inc.
www.Nexreg.com

SDS HazCom 2024 - WHMIS 2022 (Nexreg) 2025