



Technical Information

1 Product Name

Mirro-Mastic®

2 Manufacturer

Palmer Products Corporation
146 St. Matthews Ave.
Louisville, KY 40207

Phone

800.431.6151
502.893.3668

Fax

502.895.9253

Website

mirro-mastic.com

E-mail

palmer@mirro-mastic.com

3 Product Description

Basic Use

Mirro-Mastic® is a high quality adhesive mastic formulated for adhering acrylic and glass mirror to various substrates such as drywall, wood, glass, metal or tile.

4 Technical Data

Appearance

Heavy paste

Application temperature

59°F to 95°F (15°C to 35°C)

Cleanup

Mineral spirits

Color

Black

Composition and materials

Mirro-Mastic® is an asphalt base adhesive

Coverage

With **minimum** coverage, one 11 fl oz (325 ml) cartridge will install approximately 12 square feet (1.1 square meters) of mirror, one 29 fl oz (858 ml) cartridge will install approximately 30 square feet (2.8 square meters) of mirror, one gallon (3.785 L) will install approximately 130 square feet (12 square meters) of mirror and one 5 gallon (18.927 L) pail will install 640 square feet (60 square meters)

Cure time

Curing time will depend on temperature, humidity, type of substrate and amount of air that can reach the mastic

Density

No data available

Flash point

Over 160°F (71.1°C)

Packaging

11 fl oz (325 ml) cartridge (24 per case)
29 fl oz (858 ml) cartridge (12 per case)
1 gallon (3.785 L) can (4 per case)
5 gallon (18.927 L) pail

Shelf life

Two years from the production date for an unopened can
One year from the production date for an unopened cartridge

Storage

50°F to 85°F (10°C to 29.4°C)

Viscosity

No data available

VOC content

230 g/L

WARNING: All Palmer products must be used only for approved purposes, and must be applied only in accordance with Palmer's installation instructions. The user bears all risk of damage, injury or other loss arising out of any nonapproved use and/or improper installation of any Palmer product. If Palmer's installation instructions are not followed, in whole or part, for whatever reason, then mechanical fasteners of sufficient size and strength must immediately be used to insure safety of the installation pending prompt proper reinstallation by the product user. Any failure to properly utilize or apply any Palmer product may result in property damage, bodily injury or death. Palmer shall not be responsible for these or any other types of misuse of its products.