

Technical Information

1 Product Name

SuperSet Mirro-Mastic®

2 Manufacturer

Palmer Products Corporation 146 St. Matthews Ave. Louisville, KY 40207

Phone

800.431.6151 502.893.3668

Fax

502.895.9253

Website

mirro-mastic.com

E-mail

palmer@mirro-mastic.com

3 Product Description

Basic Use

SuperSet Mirro-Mastic® is a high quality low VOC, solvent-free adhesive mastic formulated for adhering acrylic and glass mirror to various substrates such as drywall, wood, glass, metal or tile

4 Technical Data

Appearance

Paste

Application temperature

59°F to 95°F (15°C to 35°C)

Cleanup

Methylethylketone (MEK) or acetone

Color

White

Composition and materials

SuperSet is a one-component elastomeric hybrid adhesive

Coverage

With **minimum** coverage, one 10.1 fl oz (300 ml) cartridge will install approximately 20 square feet (1.9 square meters) of mirror

Cure time

>2 mm/24 h @ 73.4°F (23°C) and 50% HR

Density

 1.54 ± 0.05 @ 68° F (20°C)

Flash point

No data available

Packaging

10.1 fl oz (300 ml) per cartridge (24 per case)

Shelf life

Ten months from the production date for an unopened cartridge

Storage

50°F to 85°F (10°C to 29.4°C)

Viscosity

No data available

VOC content

9 g/L



WARNING: All Palmer products must be used only for approved purposes, and must be applied only in accordance with Palmer's installation instructions. The user bears all risk of damage, injury or other loss arising out of any nonapproved use and/or improper installation of any Palmer product. If Palmer's installation instructions are not followed, in whole or part, for whatever reason, then mechanical fasteners of sufficient size and strength must immediately be used to insure safety of the installation pending prompt proper reinstallation by the product user. Any failure to properly utilize or apply any Palmer product may result in property damage, bodily injury or death. Palmer shall not be responsible for these or any other types of misuse of its products.